



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

1) International Patent Classification ⁷:

C09K 5/00, F25B 17/08

A1

(11) International Publication Number:

WO 00/31206

(43) International Publication Date:

2 June 2000 (02.06.00)

2) International Application Number: PCT/SE99/02187

3) International Filing Date: 24 November 1999 (24.11.99)

4) Priority Data:

9804034-8

24 November 1998 (24.11.98)

SE

5) Applicant (for all designated States except US): SUNCOOL AB [SE/SE]; Box 41, S-141 01 Norsborg (SE).

6) Inventors; and

7) Inventors/Applicants (for US only): JONSSON, Staffan [SE/SE]; Bohultsgatan 7, S-691 33 Karlskoga (SE). OLS-SON, Ray [SE/FI]; Mörbys 81, FIN-22240 Hammarland (FI). KÄREBRING-OLSSON, Mona [SE/FI]; Mörbys 81, FIN-22240 Hammarland (FI).

8) Agents: LINDÉN, Stefan et al.; Bergenstråhle & Lindvall AB, Box 17704, S-118 93 Stockholm (SE).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

4) Title: A CHEMICAL HEAT PUMP USING A SOLID SUBSTANCE



7) Abstract

In a chemical heat pump a substance is used which in an efficient way interacts with a volatile liquid such as water. The substance is selected considering among other things the magnitude of its ΔT and its energy content so that the heat pump becomes suited for converting low grade heat energy such as solar energy to cooling for air-conditioning and also for a simultaneous production of heat for example for use as hot tap water in houses. The heat pump can also be used in a refrigerating box. Suitable substances comprise barium hydroxide, lithium hydroxide, strontium bromide and cobalt chloride. The substance is applied as a layer (23) on the surface of a heat conducting wall (21) by applying a slurry-like mixture of the substance with the liquid when being vibrated to the wall between heat conducting flanges (25). The mixture is dried under a vacuum and is heated and is simultaneously compressed by applying an exterior pressing force. This gives a solid, well adhering layer of a substance having a high porosity which can resist a large number of cycles without any degradation of the internal structure of the layer and of its adherence to the heat conducting wall and the flanges.